



Class Builder: Klasse ZCL_PP_TOOLS anzeigen


 Muster Pretty Printer Signatur

Art	Parameter	Typisierung	Beschreibung
	IN_TABNAME	TYPE TABNAME	Tabellenname

Methode CO_READ_DB aktiv



Bildschirm

```

1_tabnamz = 01_tinnn.
WHEN 'PROJ' OR 'TCJ05'.
  1_tabnamz = 'GT_PRPS'.
WHEN 'EBAN' OR 'CRHD' OR 'T430'.
  1_tabnamz = 'GT_AFVGD'.
WHEN 'EKKO'.
  1_tabnamz = 'GT_EBAN'.
WHEN 'TCF10'.
  1_tabnamz = 'GT_FHM'.
WHEN 'CRTX'.
  1_tabnamz = 'GT_CRHD'.
WHEN 'MAKT'.
  1_tabnamz = 'GT_MARA'.
WHEN OTHERS.
  1_tabnamz = 'GT_CAUFVD'.
ENDCASE.

CONCATENATE 'GT_' in_tabname INTO 1_tabname.
CREATE DATA itx TYPE STANDARD TABLE OF (in_tabname).

ASSIGN: itx->*      TO <itx>,
        (1_tabname) TO <ity>,
        (1_tabnamz) TO <itz>.

IF NOT <itx> IS ASSIGNED OR NOT <ity> IS ASSIGNED OR
   NOT <itz> IS ASSIGNED.
  RETURN.
ENDIF.

* ...Where-Clause
co_get_sel_tab( in_tabname ).

TRY.
  IF LINES( <itz> ) > 0.
    SELECT * FROM (in_tabname) INTO TABLE <itx>
           FOR ALL ENTRIES IN <itz>
           WHERE (gt_sel_tab).
    IF sy-subrc EQ 0.
      <ity> = <itx>.
    ENDIF.
  ENDIF.

* ...Exceptions
CATCH cx_sy_dynamic_osql_semantics INTO g_cx_root.
  g_errtxt = g_cx_root->get_text( ).
CATCH cx_sy_open_sql_db INTO g_cx_root.
  g_errtxt = g_cx_root->get_text( ).
ENDTRY.

ENDMETHOD.

```

Ze 26, Sp 10

Ze 17 - Ze 65 von 65 Zeilen

E01 (1) 030 tta32 INS